

Standard Range

To meet with our philosophy to provide the best products, each pump listed in our standard pump range complies with the provisions contained in the following international standards: 73/23CEE of 19/2173, 89/336CEE of 315/89, EN60335-1, ISO 9001 (version 2000).

Features

- Glass filled polypropylene enclosure extremely shockproof and resistant to chemical aggression.
- IP 65 protection degree and class 2 electrical insulation (no earthing required)
- Extra strong and long-life squeeze tubing, always equipped with inlet-outlet fittings for fast and safe connections.
- User friendly and simple parameter settings via trimmer/pot settings.
- Easy wall mounting and removing thanks to the fixing brackets.
- Complete installation and accessory kit provided.
- Stainless detergent and rinse injection fittings provided as standard.

PR Series: Adjustable flow rated peristaltic dosing pumps.



Model	Description	Code
PR-1	Flow rate: from 0.15 to 1 l/h Pressure: 3 bar Tube: Sekobril Power supply: 230 Vac 3W	PPR0301A2Z00
PR-4	Flow rate: from 1 to 4 l/h Pressure: 0.1 bar Tube: Santoprene Power supply: 230 Vac 3W	PPR0004A1230
PR-7	Flow rate: from 1 to 7 l/h Pressure: 0.1 bar Tube: Santoprene Power supply: 230 Vac 3W	PPR0007A1Z00
PR-18	Flow rate: from 1 to 18 l/h Pressure: 0.1 bar Tube: Santoprene Power supply: 230 Vac 3W	PPR0018A1000

PRT Series: Timed peristaltic pumps with 2 timers. Powered by one solenoid valve.



Model	Description	Code
PRT-9	Flow rate: 9 l/h Pressure: 0.1 bar Tube: Santoprene Power supply: 230 Vac 3W	PRT0009A1Z00

PA Series: Peristaltic dosing pumps controlled by a conductivity probe.



Model	Description	Code
PA-9	Flow rate: 9 l/h Pressure: 0.1 bar Tube: Santoprene Power supply: 230 Vac 3W	PPA0009A1Z00